

AS_OPA4003 FleX™ OTA


Quad Operational Transconductance Amplifier



Overview

The AS_OPA4003 is four low power, high performance operational transconductance amplifiers (OTAs) in an ultra-thin, physically flexible form factor. The FleX-OPA4003 is ideal for printed and/or flexible sensor systems that require signal amplification and filtering. Operating at 2.5V, the low-power FleX-OPA4003 simplifies flexible hybrid electronics (FHE) system integration for applications including wearables, Internet of Things (IoT), and embedded sensors. Ultra-thin (25um) FleX-ICs have demonstrated flexibility below 5mm radius of curvature. Video demonstrations of FleX devices in operation can be viewed at <http://www.americansemi.com/>


The Flex-OPA4003 is fabricated in the TowerJazz CS18 180nm SOI process and converted to a flexible form factor using the American Semiconductor FleX™ Silicon-on-Polymer process.



Features and Block Diagram

Each of the four on-board OTAs are low noise and high performance to provide maximum utility in a wide range of flexible system applications.

Stability	Unity-gain; internally compensated
Open Loop Gain	85dB; typical
Gain Bandwidth	1.8MHz; typical
Slew Rate	0.9V/μs; typical
Input Range	Rail-to-rail
Output Swing	Within 200mV of supply rails
Input Offset Voltage	39 μV; typical
Low Noise	0.1Hz to 10Hz noise is just 0.3μVP-P; 1kHz noise is less than 18nV/√Hz



AS_OPA4003 FleX™ OTA

Quad Operational Transconductance Amplifier

Physical Specifications


Die Size	2.4mm X 2.4mm
Pin Count	24
Pad Openings	160um X 160um
Pad Pitch	300um
Thickness	25um
Flexible	Yes
Conformal	Yes

Process Details

Technology	TowerJazz 180nm PD-SOI
Interconnect	4-level Aluminum
Flexibility	FleX Silicon-on-Polymer

Pin List

Pin Name	Function
INN _x	Analog Input Inverting
INP _x	Analog Input Non-Inverting
OUT _x	Analog Output
ENABLE _x	Enable Input Signal
VDD	Power
VSS	Ground
x = 1, 2, 3, and 4 for individual op amps	



Ordering Information

Part Number	Description
AS_OPA4003.fxd	FleX Quad OTA flexible die with recessed Al bond pads
AS_OPA4003P.fxd	FleX Quad OTA flexible die with 10um Ni/Au plated bond pads

Contact Info

For more information or to purchase FleX products, please contact us at:

Email: sales@americansemi.com

Phone: 208.336.2773

NOTE: The information provided in this datasheet is preliminary as the product is still in testing. Changes to the final product specifications based upon the test results are possible.

American Semiconductor Inc., the American Semiconductor logo, FleX, FleX-OTA, and Silicon-on-Polymer are trademarks of American Semiconductor, Inc. All other trademarks are the property of their respective owners.